



Cycle Ergometers

Cardiorespiratory Exercise Stress Testing



The Corival cpet Cycle Ergometer is specifically designed for cardiopulmonary exercise stress testing and rehabilitation.

CORIVAL CYCLE ERGOMETER

Low step-through height provides easy access for all individuals. Optional features include the pediatric adaptation for shorter patients, large saddle and low start-up load

FEATURES

- Braking principle: Eddy current e
- RPM independent 30-150 (r.p.m.)
- 3.5" digital readout of Watts and RPM
- Accuracy r.p.m.: $\pm 2\%$ at full scale
- Workload range:
Adjustable 7-1000 W
- 750-1000 W Peak load



The Excalibur Sport is ideal for both aerobic and anaerobic training and assessment.

EXCALIBUR SPORT

The ergometer is speed independent up to 180 r.p.m. with a constant workload up to 1300 W and up to 2000 W during Wingate testing. Both racing saddle and handlebars offer a variety of position options for optimal performance.

FEATURES

- Braking principle: Eddy current
- Workload and RPM display
- Racing saddle, handlebars and toe clips are standard
- Wingate up to 2000 Watts
- Workload Programmer

SIMPLE TO ADJUST. QUICK AND EASY POSITIONING.



SPECIFICATIONS

CORIVAL CPET

ACCURACY & RANGES

- Work Load Range 7 to 750 W; 1000 W peak
- Work Load Accuracy: <100 W \pm 3 W
100 to 500 W 3%; 500 to 1000 5%
- RPM Independent 30 - 150

COMFORT

- Q-factor: 180 mm
- Handlebar adjustment angle: 360°
- Adjustability range seat: 11.8" (300 mm)
- Minimum leg length user: 25.4" (645 mm)

DIMENSIONS AND WEIGHTS

- (L x W x H) 41.3" (105 cm) x 18.1" (46 cm) x 44.9" (114 cm)
- Net weight: 138.9 lbs (63 kg)
- Maximal subject weight: 396.8 lbs (180 kg)

ENVIRONMENTAL CONDITIONS DURING USE

- Temperatures: 14° - 40°C (57° - 140°F)
- Humidity: 30% - 90% at 25° - 40°C (77° - 104°F) non condensing

ELECTRICAL POWER REQUIREMENTS

- 100 - 240 V 50/60 Hz (160 Watt)
- Power consumption: 75 VA

STANDARDS & SAFETY

- ISO 9001:2003, ISO 13485:2008
- RoHS/WEE compliant
- FDA 510K certified
- MDD 93/42/EEC
- IEC 60601-1

OPTIONS

- Programmable controller
- Blood Pressure Monitor
- Heart rate signal
- Zero watt start
- Pediatric seat, cranks and pedals
- Large saddle

EXCALIBUR SPORT

ACCURACY & RANGES

- Work Load Range: 8 to 1500 W
- Wingate up to 2500 W
- RPM Independent 25 to 180
- Work Load Accuracy: < 100 W \pm 2 W,
100 to 1500 W \leq 2% >1500 \leq 5%
- RPM Accuracy: Analog meter <2% full scale LCD Work Load Programmer \pm 1 r.p.m.
- RPM Range: Analog meter (0 to 180 r.p.m.)
- Digital LCD on Work Load Programmer (0 to 255 r.p.m.)

DIMENSIONS AND WEIGHTS

- 130 cm (51.2") x 70 cm (27.6") x 89 cm (35")
- Net weight: 100 kg (220lbs.)
- Maximal subject weight 180 kg (396lbs.)

ENVIRONMENTAL CONDITIONS DURING USE

- Temperatures: 14° - 40°C (57° - 140°F)
- Humidity: 30% - 90% at 25° - 40°C (70° - 104°F) non condensing
- Barometric Pressure: 70 KPa to 106 KPa (425 - 795 mmHg)

ELECTRICAL POWER REQUIREMENTS

- 115/230 (VAC), 50/60 (Hz)
- Power consumption: 25 VA (standby) 85 VA (1000 W Workload)

STANDARDS & SAFETY

- IEC-601-1 safety class 1, type B, TUV, BSI, PTB and FDA-510 (K)

OPTIONS

- Pedal Force Measurement
- Heart rate signal
- Double connected handlebar
- Zero watt start-up



MGC DIAGNOSTICS CORPORATION, manufactured by LODE, distributed by Medical Graphics Corporation
350 Oak Grove Parkway St. Paul, Minnesota USA 55127-8599

© 2016 MGC Diagnostics Corporation or one of its affiliates. All rights reserved.

All specifications subject to change without notice. Products may vary from those illustrated.

MGC Diagnostics and its affiliates are equal opportunity/affirmative action employers committed to cultural diversity in the workforce.

Part# 060020-001 Rev C